

The LMA-28K is a 28" 4K HD industrial monitor. The monitor has a fast response time, built-in digital noise reduction and supports 24/7 continuous play making the LMA-28K a good solution for monitoring applications.



LMA-28K Front



LMA-28K Back

Key Features

- 4K HD solution
- Fast response time
- Built-in 3D comb filter
- 3D digital noise reduction
- HDMI / VGA
- 16:9 grade A panel
- Supports 24/7 continuous
- Desk stand (Optional)
- Standard and VESA mount options

Accessories



BT7510/B
Fixed LCD / TFT Wall Mount Bracket



BT7511/B
Tiltable LCD / TFT Wall Mount Bracket



BT7518/B
Tilt & Swivel Wall Mount Bracket



BT7512/B
Single Arm Tilt & Swivel Wall Mount Bracket



BT7513/B
Double Arm Wall Mount Bracket



Specification

Model Number	LMA-28K
Size	28"
Active Display Area	648.9 (W) x 369.3 (H) mm
Display Mode	16:9
LED Type	TFT-LED
Resolution	3840 x 2160
Display Colour	1.037G
Pixel Pitch	0.248 (H) x 0.248 (V) mm
Brightness	350cd/m ²
Contrast Ratio	3000:1
Viewing Angle	178 (H) / 178 (V)
Response Time	5ms
Backlight	LED
Inputs	HDMI2.0 x1, VGA x1, DVI x1, DP x1
Outputs	Speaker 2x3W (Stereo)
Colour System	PAL / NTSC / SECAM
OSD Control	Auto adjust, Brightness, Contrast, Horizontal / Vertical position, Clock, Phase, Colour, Language
3D Comb Filter	Yes
Video Noise Reduction	Yes
Power	AC100V ~ 240V, 50/60Hz
Power Consumption	≤80W
Working Temperature	-30°C ~ 85°C
Mounting	Stand mount, VESA mount
MTBF	50000 hours
Dimensions	652.4 (W) x 386.2 (H) mm
Weight	8.06 Kg

Genie Access reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.

Dimensions (mm)

