

# LME43-4K

## 43" 4K LED Panel

Panel Type	LED
Case Type	Metal
Maximum Resolution	3840 (H) x 2160 (V)
MTBF	50,000 hrs
Active Display Area	941.2 × 529.4 (H×V)
Pixel Pitch	0.2451x0.2451 mm
Bezel Thickness	Lef / Right / Top 7.9mm, Bottom 7.9mm
Contrast Ratio	4000 : 1
Brightness	350 CD/M2
Response Time	8m.sec (G to G)
Viewing Angle	178 / 178° (H/V)
Display Colours	1.07B (10-bit)
Video Synchronisation	Yes
PC Compatibility	Yes
Aspect Ratio	16:9 / 4:3
VGA Auto Frequency Correction	N/A
Speakers	2
Sound Demodulation	Yes
Mute	Yes
Work Humidity	5% - 90%
Work Temperature	0 - 50 °C
Volume +/- Power On/Off	Yes



### IN / OUT INTERFACE

Video Interface	1 x HDMI v2.0 input, 2 x HDMI v1.4 input, 1 x DP v1.2 input
Audio	1 x Output
Termination	N/A
Certification	CE, FCC, ROHS
VESA	400 x 400
Stand Type	Without
Colour	Black
Button Position	Bottom Middle in the Back Case
Packing Dimensions	1050mm x 110mm x 650mm
Net/Gross Weight	10.45kg/12.1kg

### POWER

Power Supply	N/A
Power Consumption	<= 80W
Voltage:	AC110~240V
Power Interface	AC110~240V

### OSD CONTROLS

Contrast, Brightness, DCR, Saturation, OSD position, Gamma, Color temp, Hue, Low blue light, Sharpness, Noise reduction, Aspect Ratio, Mute, Volume, Multi-Window, OSD position

### OSD LANGUAGE

English, French, Russian, Spanish, German, Italian, Portuguese, Turkish, Danish, Polish and Dutch

### ACCESSORIES

Power cord, User's guide, HDMI cable, Remote control

