

DA381

24V AC 4A Power supply
With two 2A output

This simple range of multipurpose power supplies is available metal cased or within an IP66 weather resistant enclosure. They provide 4A of 24V AC via individually fused outputs.

Manufactured and tested in Britain, this range of power supplies has a five year warranty, allowing installers to fit and forget. It is ideal for where high reliability is required and where companies may have service or maintenance contracts for long periods of time.

Typical uses include powering CCTV cameras and camera housing heaters.

Output			
Voltage	24V AC		
Current	2 x 2A		
Connection type	PCB terminal block (2.5mm ²)		
Fused	20 x 5mm 2A quick blow glass fuse		
Input			
Voltage	DA381	DA381-110V	
	230V AC @ 50Hz (+/- 10%)	110V AC @ 50Hz (+/- 10%)	
Power consumption	< 125VA		
Connection type	10mm ² internal terminal block (3 x 1.5mm ² or 2 x 2.5mm ²)		
Fused	3A Mains fuse (BS1362)		
Environmental			
Operating temperature	-10°C to +40°C		
Storage temperature	-20°C to +50°C		
Operating relative humidity	Maximum 95% non-condensing		
Ingress protection	DA381	DA381-IP66	DA381-P
	DA381-110V	DA381-110V-IP66	
	IP20	IP66	N/a
Dimensions*			
	DA381	DA381-IP66	DA381-P
	DA381-110V	DA381-110V-IP66	
Width	120mm	150mm	130mm
Height	200mm	250mm	230mm
Depth	70mm	100mm	60mm
Weight	< 2.1Kg	< 2.1Kg	< 2.0Kg
Enclosure material	Mild steel	Acrylonitrile Butadiene Styrene (ABS)	Mild steel
Finish	Powder coated RAL9016 (white)	RAL9003 (Grey)	Powder coated RAL9016 (white)
Other			
Estimated operations before failure (MTBF)	65,000 hours		
CE Approved	Yes		

*(+/- 2mm)